



Kora Inverter Series

Serie Kora Inverter

MODEL / MODELO: HWDKC_S / HWDKC_AS

SPECIFICATIONS / ESPECIFICACIONES

Model			HWDKC30S/HRDKC30AS	HWDKC36S/HRDKC36AS
Power Supply		V-Ph-Hz	208V~230V,60Hz	208V~230V,60Hz
Cooling	Capacity	Btu/h	30000	36000
	Rated current	A	12.8	14.8
	SEER	Btu/w	18.8	17.6
Heating	Capacity	Btu/h	31000	33500
	Rated current	A	12.0	13.8
	HSPF		12.3	9.6
Compressor	Type		Rotary	Rotary
	Brand		Hitachi	Hitachi
Minimum Circuit Ampacity		A	1.55	1.75
Max Fuse		A	30	30
Indoor air flow		m3/h	1800	1800
Indoor noise level (Hi/Mi/Lo/silence)		dB(A)	50/45/40/38	50/45/40/38
Outdoor noise level			60	60
Indoor unit	Dimension(W*D*H)	mm	1280x360x260	1280x360x260
	Dimension(W*D*H)	inch	50 3/8x14 3/16x10 1/4	50 3/8x14 3/16x10 1/4
	Packing (W*D*H)	mm	1385x435x325	1385x435x325
	Packing (W*D*H)	inch	54 1/2x17 1/8x12 13/16	54 1/2x17 1/8x12 13/16
	Net/Gross weight	Kg	18.0 / 21.5	19.5 / 23.0
	Net/Gross weight	lbs.	39.6 / 47.3	42.9 / 50.7
Outdoor unit	Dimension(W*D*H)	mm	885x795x366	885x795x366
	Dimension(W*D*H)	inch	34 7/8x31 5/16x14 3/8	34 7/8x31 5/16x14 3/8
	Packing (W*D*H)	mm	1050x890x500	1050x890x500
	Packing (W*D*H)	inch	41 11/32x35x19 11/16	41 11/32x35x19 11/16
	Net/Gross weight	Kg	58 / 63	60 / 65
	Net/Gross weight	lbs.	72.7 / 79.3	97 / 105
Refrigerant piping	Liquid side / Gas side	inch	3/8" / 5/8"	3/8" / 5/8"
Refrigerant			R410A	R410A
Refrigerant charge volume		g	2070	2250
Room Temperature	Cooling	(°C / °F)	-15°C-46°C; (5°F-115°F)	-15°C-46°C; (5°F-115°F)