



Multi Zone Inverter Series High Wall

Serie MM de Inverter Multizona

MODEL / MODELO: MMAHC_S

SPECIFICATIONS / ESPECIFICACIONES

Model			MMAHC09S	MMAHC12S	MMAHC18S	MMAHC24S
Power supply		Ph-V-Hz	208-230~1-60	208-230~1-60	208-230~1-60	208-230~1-60
Indoor fan motor	Model		ZKFP-20-8-6	ZKFP-20-8-6	ZKFP-58-8-1	ZKFN-120-8-2
	RLA	A	0.25	0.25	0.4	0.45
Indoor air flow (Hi/Mi/Lo)		m3/h	450 / 348 / 240	520 / 360 / 250	950 / 620 / 520	1050 / 800 / 550
Indoor air flow (Hi/Mi/Lo)		CFM	264 / 205 / 141	306 / 212 / 147	559 / 365 / 306	618 / 471 / 324
Indoor noise level (Hi/Mi/Lo)		dB(A)	39 / - / 24.5	39 / - / 25	45.5 / - / 34.5	50 / - / 35.5
Indoor unit	Dimension (W*D*H)	mm	802 x 189 x 297	802 x 189 x 297	1080 x 226 x 335	1080 x 226 x 335
	Dimension (W*D*H)	inch	31.57 x 7.44 x 11.69	31.57 x 7.44 x 11.69	42.52 x 8.90 x 13.19	42.52 x 8.90 x 13.19
	Packing (W*D*H)	mm	875 x 285 x 375	875 x 285 x 375	1155 x 415 x 315	1155 x 415 x 315
	Packing (W*D*H)	inch	34.45 x 11.22 x 14.76	34.45 x 11.22 x 14.76	45.47 x 16.34 x 12.40	45.47 x 16.34 x 12.40
	Net/Gross weight	Kg	8.2 / 10	8.2 / 10	13.2 / 16.8	13.2 / 16.8
	Net/Gross weight	lbs.	18.1 / 22.0	18.1 / 22.0	29.1 / 37.0	29.1 / 37.0
Design pressure		PSIG	550 / 340	550 / 340	550 / 340	550 / 340
Refrigerant piping	Liquid side/ Gas side	mm	Φ6.35/Φ9.52 (1/4"/3/8")	Φ6.35/Φ12.7 (1/4"/1/2")	Φ6.35/Φ12.7 (1/4"/1/2")	Φ9.52/Φ15.9 (3/8"/5/8")
Thermostat type			Remote Control	Remote Control	Remote Control	Remote Control
Operation temperature	Indoor(cooling/heating)	°C	17~32 / 0~30	17~32/0~30	17~32/0~30	17~32/0~30
	Indoor(cooling/heating)	°F	62~90 / 32~86	62~90/32~86	62~90/32~86	62~90/32~86
Application area		m ² / ft ²	12-17.6 / 129-189	16-23.4 / 172-252	23.3-34.2 / 251-368	30.6-44.9 / 330-484