



**PIPE KIT
INCLUDED**

Fixed Speed Mini-Split

Mini-Split de velocidad fija

MODEL / MODELO: MWFOT_SA / MRFOT_ASA

SPECIFICATIONS / ESPECIFICACIONES

Model		MWFOT12SA/MRFOT12ASA	
	Power supply	V,Hz,Ph	115V,60Hz, 1Ph
Cooling	Capacity	Btu/h	12500
	Rated current	A	10.6
	EER	W/W	3
	Max. current	A	12.5
	Starting current	A	54
Compressor	Type		ROTARY
	Brand		GMCC
	Rated current(RLA)	A	9.5
	Locked rotor Amp(LRA)	A	54
	Capacitor	uF	70
	Refrigerant oil/oil charge	ml	ESTER OIL VG74 . 350 . MI
	Indoor air flow (Hi/Mi/Lo)	m3/h	559/441/353
	Indoor noise level (Hi/Mi/Lo)	dB(A)	40.8/34.6/27.9
Indoor unit	Dimension(W*D*H)	mm	805x194x285
	Packing (W*D*H)	mm	870x270x360
	Net/Gross weight	Kg	8.3/10.5
	Outdoor noise level	dB(A)	53.7
Outdoor unit	Dimension(W*D*H)	mm	700x275x550
	Packing (W*D*H)	mm	815x325x615
	Net/Gross weight	Kg	25.6 / 27.9
	Refrigerant type	g	R410A/500g
	Design pressure	MPa	4.2/1.5
Refrigerant piping	Liquid side/ Gas side	mm(inch)	Φ6.35/Φ9.52(1/4"/3/8")
	Max. refrigerant pipe length	m	20
	Max. difference in level	m	8
	Thermostat type		Remote Control
	Operation temperature	°C	17-30
Room temperature	Indoor (cooling/ heating)	°C	17-32/----
	Outdoor (cooling/heating)	°C	18-43/----
	Application area	m2	17-24

Features and Benefits



Emergency Using



Mute Operation



Refrigerant
Leakage Detect



Louver Position
Memory



Manual ON/OFF



Fire-proof
Electric Box



High Density
Filter