- 17+ SEER on ALL capacities
- 4-meter pipe kit standard
- Acrylic Panel with 4H hardness for increased durability while coming with the sheen of Obsidian
- Improved condensing unit design for easier maintenance 115 V

Vision Inverter Series






| Model | | | MWVIT09SA/MRVIT09ASA | MWVIT12SA/MRVIT12ASA | |
|--------------------|------------------------------|------------|-------------------------|-------------------------|--|
| | Power supply | V-Hz-Ph | 115V -60Hz-1ph | 115V -60Hz-1ph | |
| Cooling | Capacity | Btu/h | 9500 | 12000 | |
| Cooling | SEER | Btu/w | 17 | 17 | |
| | Liquid side/ Gas side | mm (inch) | Ф6.35/Ф9.52 (1/4"/3/8") | Ф6.35/Ф12.7 (1/4"/1/2") | |
| Refrigerant piping | Max. refrigerant pipe length | m - ft | 25 - 82 | 25 - 82 | |
| | Max. difference in level | m - ft | 10 - 33 | 10 - 33 | |
| Application area | | m2 / sq.ft | 12-17.6 / 129-189 | 16-23.4 / 172-252 | |

| | | Model | | MWVIT09S/MRVIT09AS | MWVIT12S/MRVIT12AS | MWVIT18S/MRVIT18AS | MWVIT24S/MRVIT24AS |
|--|----------------------|------------------------------|------------|----------------------------|----------------------------|----------------------------|----------------------------|
| | Power supply V-Hz-Pl | | V-Hz-Ph | 208-230V-60Hz-1ph | 208-230V-60Hz-1ph | 208-230V-60Hz-1ph | 208-230V-60Hz-1ph |
| | Cooling | Capacity | Btu/h | 9000 | 12000 | 17000 | 22000 |
| | | SEER | Btu/w | 18 | 17 | 17 | 18 |
| | Refrigerant piping | Liquid side/ Gas side | mm(inch) | Ф6.35/Ф9.52 (1/4"/3/8") | Ф6.35/Ф12.7 (1/4"/1/2") | Ф6.35/Ф12.7 (1/4"/1/2") | Ф9.52/Ф15.9 (3/8"/5/8") |
| | | Max. refrigerant pipe length | m - ft | 25 - 82 | 25 - 82 | 30 - 98 | 30 - 98 |
| | | Max. difference in level | m - ft | 10 - 33 | 10 - 33 | 20 - 66 | 20 - 66 |
| | Application area m2 | | m2 / sq.ft | 12-17.6 / 129-189 | 16-23.4 / 172-252 | 23.3-34.2 / 251-368 | 30.6-44.9 / 330-484 |



Golden Fin

Effectively prevent bacteria breeding and improve heat transfer efficiency. The unique anti-corrosive golden coating on the condenser can withstand the salty air rain and other corrosive elements.



position as you set last time

when the unit turned on.



Refrigerant Leakage Detect

Indoor unit will show error code "EC" and stop automatically when refrigerant leakage is detected. This function can better protect compressor being damaged by high temperature due to refrigerant leakage.





12 Grades Indoor Fan Speeds

Up to 12 grades indoor fan speeds, ensure more accurate control and bring more comfortable air flow.



Sleep Mode

The function enables the air conditioner to automatically increase cooling or decrease heating 1°C per hour for the first 2 hours, then holds steady for the next 5 hours, after that it will switch off. This function maintains both energy saving and comfort at night.



Self-diagnosis and Auto-protection

Once abnormal operation or parts failure happen, the unit will shut off automatically to protect the system. Meanwhile it will indicate protection or error code for fast service.





R~410A

Turbo **TURBO**

This function gives you a boost in cooling and heating power for a period, and makes the room cool down or heat up rapidly.



2-way Draining

Both left and right sides of indoor unit are possible for drainage hose connection, easy for installation.

